.0312″ cr

10.9060″

6.8125″

6.9375″ finished liner width

LEADING LABEL EDGE

UNLEADED FORMULA
BLEIFREIE FORMEL

MAKES UP TO 110 OCTANE* RON

Race Gas®

Race Fuel Concentrate

for Professional Competition
OFF ROAD USE ONLY

DANGER!
FLAMMABLE / BRENNBAR
POISON / GIFTIG

**Based on independent laboratory testing. / *Angaben basieren auf unabhängigen Labortests.*

946 mL

Do not smoke. Do not swallow. Do not get in eyes or on skin or clothing. Do not breathe fumes.

Use only in well ventilated area. Keep away from flames, such as pilot light, and any object that sparks, such as an electric motor. Keep out of reach of children. Wear a MSHA/NIOSH approved (or equivalent) full-facepiece airline respirator in the positive pressure mode. Wear impervious gloves to prevent contact with the skin.
Use only in a well-ventilated area.

FIRST AID TREATMENT:

Contains 2-methoxy-2-methyl propane (1634-04-4) Naphtha (petroleum), hydrotreated light (64742-49-0), Methylcyclopentadienyl manganese tricarbonyl (12108-13-3), Toluene (108-88-3), Petroleum hydrocarbon (64742-94-5)
If swallowed, call a Poison Control Centre or doctor immediately. Do NOT induce vomiting.
If in eyes or on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person into fresh air.

Race Gas® is specially formulated to transform unleaded gasoline from your local gas station into high octane racing fuel suitable for competition and professional use. Laboratory tested and race proven, mix Race Gas Race Fuel Concentrate with fresh quality gasoline (91-98 octane) to raise the final octane to as high as 110 (Research Octane rating). Never run out of race fuel again.

Nicht rauchen. Nicht verschlucken. Nicht in die Augen, auf die Haut oder Kleidung gelangen lassen. Dämpfe nicht einatmen.

Nur in gut belüfteten Bereichen verwenden. Von Flammen, wie z. B. einer Zündflamme, und allen Gegenständen, die Funken erzeugen, wie z. B. einem Elektromotor, fernhalten. Außerhalb der Reichweite von Kindern aufbewahren. Tragen Sie ein zugelassenes Vollmasken-Atemschutzgerät im Überdruckmodus. Tragen Sie undurchlässige Handschuhe, um den Kontakt mit der Haut zu vermeiden. Nur in einem gut belüfteten Bereich verwenden.

ERSTE HILFE:

Enthält 2-Methoxy-2-methylpropan (1634-04-4) Naphtha (Erdöl), mit Wasserstoff behandeltes Leichtbenzin (64742-49-0), Methylcyclopentadienylmangantricarbonyl (12108-13-3), Toluol (108-88-3), Erdölkohlenwasserstoff (64742-94-5).
Bei Verschlucken sofort eine Giftnotrufzentrale oder einen Arzt anrufen. KEIN Erbrechen herbeiführen.
Bei Berührung mit den Augen oder der Haut gut mit Wasser abspülen. Bei Verschmutzung der Kleidung: Kleidung ausziehen. Wenn eingeatmet, Person an die frische Luft bringen.

Race Gas® ist speziell gestaltet, um bleifreies Benzin von Ihrer örtlichen Tankstelle in hochoktaniges Rennbenzin zu verwandeln, das für den Wettbewerb und den professionellen Einsatz geeignet ist. Laborgeprüft und rennerprobt. Mischen Sie Race Gas Race Fuel Concentrate mit frischem Qualitätsbenzin (91-98 Oktan), um die Oktanzahl auf bis zu 110 (ROZ) zu erhöhen. Mischen Sie ihr individuelles Rennbenzin - egal wann und wo.

This blend chart presumes fresh and properly marked unleaded gasoline fuels from your local gasoline station. An example of how to blend Race Gas: To make 1 Liter of 101 octane fuel starting with a base of 95 octane from your local gasoline station add 24 mL of Race Gas Fuel Concentrate to the 95 octane fuel and blend thoroughly.

BLENDING CHART / 1-Liter FUEL
Desired Octane RON

Base Octane RON	95	97	99	101	103	105	107	109	112
	ML OF RACE GAS TO ADD PER LITER								
91	16	24	31	39	47	55			
95			16	24	31	39	47	55	
98				16	24	31	39	47	55

Diese Mischtabelle setzt frische und ordnungsgemäß gekennzeichnete bleifreie Benzinkraftstoffe von Ihrer örtlichen Tankstelle voraus.

Ein Beispiel für die Mischung von Race Gas: Um aus 1 Liter Benzin mit 95 Oktan (ROZ) 1 Liter Rennbenzin mit 101-Oktan herzustellen, fügen Sie 24 ml Race Gas Fuel Concentrate hinzu und mischen Sie gründlich.

Do not add more than 55 mL of Race Gas Fuel Concentrate per Liter of base fuel.
We have tested blended octane levels up to 112 but recommend blending no higher than 110.

Using Race Gas in your engine will not harm oxygen sensors and/or catalytic converters.
SHAKE BEFORE USE
DO NOT EXPOSE TO DIRECT SUNLIGHT
STORE BLENDED FUEL IN UV PROTECTED CONTAINER

Hinweis Überdosierung: Geben Sie nicht mehr als 55 ml Race Gas Fuel Concentrate pro Liter Basiskraftstoff hinzu. Wir haben Mischungen mit einer Oktanzahl von bis zu 112 getestet, empfehlen aber, nicht mehr als 110 zu mischen. Die Verwendung von Race Gas ist unschädlich für Lambdasonden und Katalysatoren.

VOR GEBRAUCH SCHÜTTELN
NICHT DIREKTER SONNENEINSTRAHLUNG AUSSETZEN
KRAFTSTOFFGEMISCH IN EINEM UV-GESCHÜTZTEM BEHÄLTER AUFBEWAHREN

Check this out!

Made in the USA

Part # CA100032
U.S. Pat. 9,644,162,B2

To order more or questions:
(855)-**RACE GAS** (722-3427)
or visit **www.race-gas.com**

Motorsports Fuel & Equipment, Inc.
2180 Cty Road 42W
Burnsville, MN 55337

8 52770 00409 8

Cust. Motorsports Fuel & Equipment Job Desc. 32oz Race Gas Label Bilingual Date

Spec # Job # Proof #

Colors: 1505, 447, 185, 072, dieline

Finished Wind Direction

Please check proof carefully. Approved proof dictates content of final output. Commerce Label cannot be held responsible for errors not marked by customer on a signed approved proof. PDF cannot be used for color approval, please refer to an official pantone color guide for spot color match.

Approved ☐
Approved With Change ☐
Change And Re-Proof ☐

Customer Signature:

COMMERCE
COMMERCE LABEL, INC.
ph 763-533-2226 • fax 763-533-3775
www.commercelabel.com

Barcode Disclaimer: UPC and EAN sizes are referred to as magnifications or magnification factors. The industry standard minimum size of a UPC/EAN is 80% magnification factor or .988 inches wide (from the left edge of first bar to the far right edge of last bar). Commerce Label does not guarantee scannability of UPC/EANs that are sized smaller than stated minimum size standards.